

Speedrooter 92™

Job Tested Tough

Contractors know that the Speedrooter really can take a beating – from its frame braced at key stress points, to General's exclusive Flexicore® wire rope center cable that's so tough it carries a one year warranty.

The Speedrooter 92's field tested design offers easy handling. One person can easily load it onto a truck, as the machine slides smoothly from the loading wheel to the handle to the stair climbers and finally to the wheels. The adjustable height handle can be reset to be three inches longer, or more compact, depending upon your preference.

With the driving and pulling power for long, tough jobs, General's Power Cable Feed easily handles 3/4", 5/8", and 1/2" cables. To adjust to different cable sizes, simply turn the knob on top of the feed. The screwdriver stays in the tool box.

A large drum holds 100 feet of 3/4" or 5/8" Flexicore® cable. For smaller lines, you can switch to a small drum that holds 100 feet of 1/2" cable. Both drums have a see-through inner cage, so you can quickly see how much cable is left in the drum.



One person easily loads the Speedrooter 92 onto a truck. The swept-back handle and loading wheel give you the needed leverage.

General
PIPE CLEANERS
www.drainbrain.com

Speedrooter 92™ Units

Complete and ready to operate

- PS92-A** With 100 ft. x 3/4" (100EM5) cable in large drum, 100 ft. x 1/2" (100EM3) cable in small drum, and COCS combination cutter set.
- PS92-C** 100 ft. x 3/4" (100EM5) cable and SRCS cutter set.
- PS92-E** With 100 ft. x 5/8" (100EM4) cable and SRCS cutter.



Greatly increases the efficiency of power cable feed by reducing cable whipping and drag. Keeps your hands off of the spinning cable. Tube is 30" long. Five foot extensions are made of rigid conduit with a flexible spring end.



Equipped with 10" heavy-duty wheels, stair climbers, tool box, and ground fault circuit interrupter.



V-belt stair climbers like the ones used to move heavy furniture and appliances let you take the Speedrooter 92 up a flight of stairs yourself.



Small drum holds up to 100 ft. of 1/2" Flexicore cable.



Flexicore® Wire Rope Center Cables

Heavy gauge wire is coiled around 49 strand wire rope and then heat treated. This cable has unequalled strength and the right amount of flexibility. It's so tough it has a one year warranty against defect or breakage.

Specifications:

Weight:

115 lbs. (52 kg) without cable

Dimensions:

26" deep, 22" wide, 41" high (66 cm x 56 cm 104 cm).

Drums:

Large drum holds 100 ft. x 3/4" or 5/8" cable (30 m x 19 mm or 17 mm).

Optional small drum holds 100 ft. x 1/2" cable (30 m x 12.7 mm).

Drum Removal:

Loosen two knobs, remove ringbolt, and lift off.

Motor:

1/2 hp with capacitor, forward-off-reverse switch, 20 ft. power cord and ground fault circuit interrupter.

Foot Switch:

Pneumatic, with no electrical contact between pedal and motor.

Power Cable Feed

Drives and retracts at variable speed of up to 20 ft. per minute.

Wheels:

10" Heavy-duty wheels with roller bearings.

Stair Climbers:

Heavy-duty V-belts running on nylon rollers.

Wheel Brake:

Keeps machine in place on the job or in the truck.

Truck Loading Wheel:

Enables one person to lift machine onto bed of truck.

Tool Box:

Attached to rear of machine. Holds all cutters except Flexible leader.

Leather Gloves:

With double-reinforced palm for hand protection when guiding cable.

Cables:


Left wound Flexicore® wire rope center 3/4" diameter for 4" to 10" lines and 3" lines without sharp bends; 5/8" diameter for 3" to 6" lines; 1/2" diameter for 2" to 3" lines.

Cutters:

See below.

Cutter Set for 5/8" and 3/4" cables

Additional Cutter Set for 1/2" cables



LE-3 Flexible Leader, 26" long



LE-1 Flexible Leader, 13" long

General **General Wire Spring Co.**
PIPE CLEANERS
 1101 Thompson Avenue • McKees Rocks, PA 15136 USA
 800-245-6200 or 412-771-6300 • Fax: 412-771-2771
 www.drainbrain.com • e-mail: info@drainbrain.com

The toughest tools down the line.™